

## DATA SHEET

### **ECOSEAL – Block paving sealer - 0 VOC's. (High solids)**

#### **DESCRIPTION**

A safe ORGANIC SOLVENT FREE block paving sealer  
A single part acrylic co-polymer resin suspended in a non organic solvent  
Prevents penetration of dirt, oil and fuels  
Protects against frost and reduces surface deterioration  
Environmentally friendly  
Stabilises/ bonds jointing sand (block paving) – Inhibits weed, moss, algae and fungus growth

#### **USE**

Ready to use for sealing porous cement block paving

#### **COLOUR**

Milky in appearance and becomes clear as product dries. Enhances colour slightly

#### **PACK SIZE**

20 litre UN containers

#### **SURFACE FINISH**

Matt (slight sheen) 2 coats  
Glossier effect 3+ coats

#### **SPREADING RATE**

Depending on surface type, porosity and application method  
2 coats for best results  
80-100 sq mtr per 20ltr when spraying block paving, more when brushing or rolling

#### **DRYING TIME**

Dry to walk on usually within 2hr - During normal temps' 10°C+  
Lower temps and areas in the shade will extend drying time  
Recoat when dry  
Do not park vehicles on surface for 48 hrs  
Full cure approximately 7-10 days

#### **PREPARATION**

All surfaces must be clean, dry and be free from loose and flaking material, dirt, grease and vegetative growth.

#### **APPLICATION**

Course droplet low level spray, broom, brush or roller  
\*Avoid over flooding surface  
\* Brush, broom or roller out pooled sealer  
Do not leave pooled sealer to cure

**CLEANING** - For cleaning equipment use water

#### **PRECAUTIONS**

Wear gloves and eye protection

In case of contact with eyes, rinse immediately with water and seek medical advice  
Remove splashes from the skin with soap and water  
Keep out of reach of children

**GENERAL INFORMATION**

ODOURLESS

NON FLAMMABLE

NON HAZARDOUS

0 VOC'S

Do not use below 8 °C. Protect stored product from frost and freezing

Do not seal wet or damp surfaces

Do not start sealing if rain is imminent

Do not use chlorine, bleach, sodium hypochlorite, acid, Paveclear or Paveclean chemicals prior to sealing with ECOSEAL – Block paving sealer

The specification and coverage rates are given in good faith and are based on our experience and knowledge but without liability

As Sealers Direct has no direct control over the methods employed by the user in applying its products, any warranty either written or implied is given in good faith and can only cover the material itself

If in doubt regarding any of the above points please contact us

A Material Safety Data Sheet is available on request

**[www.sealersdirect.co.uk](http://www.sealersdirect.co.uk)**