

DATA SHEET

ECOSEAL Ultra Block paving sealer - (High solids)

DESCRIPTION

A safe ORGANIC SOLVENT FREE block paving sealer

A single part acrylic co-polymer resin suspended in a non organic solvent

Prevents penetration of dirt, oil and fuels

Protects against frost and reduces surface deterioration

Environmentally friendly

Stabilises/ bonds jointing sand (block paving) – Inhibits weed, moss, algae and fungus growth

USE

Ready to use for sealing porous cement block paving

COLOUR

Milky in appearance and becomes clear as product cures. Virtually invisible or invisible

PACK SIZE

20 litre

SPREADING RATE

2+ coats for best results

Depending on substrate porosity and application method

80-100 m² approx per 20 ltr drum when spraying, more when brooming, brushing or rolling

DRYING TIME

Dry to walk on usually within 2hr - During normal temps' 10°C+

Lower temps and areas in the shade will extend drying time

Recoat when dry

Do not park vehicles on surface for 24 hrs

Full cure approximately 3-7 days

PREPARATION

All surfaces & jointing sand must be clean, dry and be free from loose and flaking material, dust, dirt, grease and vegetative growth.

APPLICATION

Course droplet low level spray, broom, brush or roller

*Avoid over flooding surface

* Brush out pooled sealer

Do not leave pooled sealer to cure

CLEANING - For cleaning equipment use water

PRECAUTIONS

Wear gloves and eye protection

In case of contact with eyes, rinse immediately with water and seek medical advice

Remove splashes from the skin with soap and water

Keep out of reach of children

GENERAL INFORMATION

ODOURLESS

NON FLAMMABLE

NON HAZARDOUS

0 VOC'S

Do not use below 8°C. Protect stored product from frost and freezing

Do not seal wet or damp surfaces

Do not start sealing if rain is imminent

Do not use chlorine, bleach, sodium hypochlorite, acid, Paveclear or Paveclean chemicals prior to sealing with ECOSEAL Ultra Block paving sealer

The specification and coverage rates are given in good faith and are based on our experience and knowledge but without liability

As Sealers Direct Ltd has no direct control over the methods employed by the user in applying its products, any warranty either written or implied is given in good faith and can only cover the material itself

If in doubt regarding any of the above points please contact us

A Material Safety Data Sheet is available on request