

DATA SHEET

ECOSEAL Ultra Clear TARMAC BINDER sealer - 0 VOC's (ultra high solids)

DESCRIPTION

A highly durable, solvent free, clear ULTRA HIGH solids tarmac binder sealer
Waterproofs to resist the formation of moss, lichen and weed growth
Prevents penetration of dirt, oil and fuels
Protects against frost and reduces surface deterioration
Environmentally friendly

USES

Ready for use as a binding/ sealer aid for old new Tarmac/ Macadam

COLOUR RANGE

Milky white in appearance, dries clear

PACK SIZE

20 litre containers

SPREADING RATE

80-100 square metres per 20 litres. Apply 2 coats for best results.

DRYING TIME

Dry to walk on usually within 2hr - During normal temps
Lower temps and areas in the shade will extend drying time
Recoat when dry
Do not park vehicles on surface for 48 hrs

PREPARATION

All surfaces should be free from loose and flaking material, dirt, grease and vegetative growth. Any debris may be removed by vacuum or pressure cleaning with air or water.

APPLICATION

Course droplet low level spray, broom, brush or roller
*Avoid over flooding surface
* Brush, broom or roller out pooled sealer
Do not leave pooled sealer to cure

CLEANING

For cleaning equipment use water

PRECAUTIONS

NON FLAMMABLE

Do not use below 8 °C. Protect stored product from frost and freezing
For your protection and safety, wear gloves, overalls, and eye protection
Keep children and animals away from sealed surface till dry
Be aware that sealed tarmac will repel surface water
Do not allow sealer to pool - Do not seal wet or damp tarmac
Do not start sealing if rain is imminent
Do not eat, drink, or smoke when using
Do not use chlorine, bleach, sodium hypochlorite, acid, Paveclear or Paveclean chemicals prior to sealing with ECOSEAL Ultra Clear TARMAC BINDER sealer
In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Remove splashes from the skin with soap and water

The specification and coverage rates are given in good faith and are based on our experience and knowledge but without liability

As Sealers Direct has no direct control over the methods employed by the user in applying its products, any warranty either written or implied is given in good faith and can only cover the material itself

If in doubt regarding any of the above points please contact us

A Material Safety Data Sheet is available on request

www.sealersdirect.co.uk