

DATA SHEET

ECOSEAL Ultra HD – Concrete sealer - (Ultra High solids)

DESCRIPTION

A safe ORGANIC SOLVENT FREE Concrete sealer
A single part acrylic co-polymer resin suspended in a non organic solvent
Prevents penetration of dirt, oil and fuels
Protects against frost and reduces surface deterioration
Environmentally friendly
Heavy duty

USE (exterior and interior)

Ready to use for sealing concrete screeds/slabs/products/architectural concrete

COLOUR

Milky in appearance and becomes clear as product dries. Minimal colour enhancement

PACK SIZE

20 litre

SURFACE FINISH

Matt 2 coats
Glossier effect 3 coats Cures
clear

SPREADING RATE

Depending on surface type, porosity and application method 2
coats for best results
80-100 m² per 20 ltr when spraying, more when brushing or rolling

DRYING TIME

Dry to walk on usually within 2hr - During normal temps' 10°C+
Lower temps and areas in the shade will extend drying time Recoat
when dry
Do not park vehicles on surface for 48 hrs Full
cure approximately 3 days

PREPARATION

All surfaces must be clean, dry and be free from loose and flaking material, dust, dirt,
grease and vegetative growth.

APPLICATION

Course droplet low level spray, broom, brush or roller
* Avoid over flooding surface
* Brush out pooled sealer
Do not leave pooled sealer to cure

CLEANING - For cleaning equipment use water

PRECAUTIONS

Wear gloves and eye protection
In case of contact with eyes, rinse immediately with water and seek medical advice
Remove splashes from the skin with soap and water
Keep out of reach of children

GENERAL INFORMATION

ODOURLESS

NON FLAMMABLE

NON HAZARDOUS

0 VOC'S

Do not use below 8°C. Protect stored product from frost and freezing

Do not seal wet or damp surfaces

Do not start sealing if rain is imminent

Do not use chlorine, bleach, sodium hypochlorite, acid, Paveclear or Paveclean chemicals prior to sealing with ECOSEAL Ultra HD – Concrete sealer

The specification and coverage rates are given in good faith and are based on our experience and knowledge but without liability

As Sealers Direct has no direct control over the methods employed by the user in applying its products, any warranty either written or implied is given in good faith and can only cover the material itself

If in doubt regarding any of the above points please contact us

A Material Safety Data Sheet is available on request