

## DATA SHEET

### **ECOSEAL Ultra HD Imprinted concrete sealer - (Ultra High solids)**

#### **DESCRIPTION**

A safe ORGANIC SOLVENT FREE Imprinted Concrete Sealer  
A single part acrylic co-polymer resin suspended in a non organic solvent  
Prevents penetration of dirt, oil and fuels  
Protects against frost and reduces surface deterioration  
Environmentally friendly  
Heavy duty

#### **USE**

Ready to use for sealing Pattern Imprinted Concrete

#### **COLOUR**

Milky in appearance, becomes clear as product cures. Minor colour enhancement

#### **PACK SIZE**

20 litre

#### **SURFACE FINISH**

Matt (slight sheen) 1 coat Glossier  
effect 2 coats

#### **SPREADING RATE**

Depending on surface type, porosity and application method 2  
coats for best results  
80-100 m<sup>2</sup> per 20 ltr when spraying, more when brushing or rolling

#### **DRYING TIME**

Dry to walk on usually within 2hr - During normal temps' 10°C+  
Lower temps and areas in the shade will extend drying time Recoat  
when dry  
Do not park vehicles on surface for 48 hrs Full  
cure approximately 3 days

#### **PREPARATION**

All surfaces must be clean, dry and be free from loose and flaking material, dust, dirt,  
grease and vegetative growth. Sealed surfaces should be keyed.

#### **APPLICATION**

Course droplet low level spray, broom, brush or roller  
\* Avoid over flooding surface  
\* Brush out pooled sealer  
Do not leave pooled sealer to cure

**CLEANING** - For cleaning equipment use water

#### **ADVISORY:**

Product may bead on existing sealed surfaces

#### **PRECAUTIONS**

Wear gloves and eye protection  
In case of contact with eyes, rinse immediately with water and seek medical advice  
Remove splashes from the skin with soap and water  
Keep out of reach of children

## **GENERAL INFORMATION**

ODOURLESS

NON FLAMMABLE

NON HAZARDOUS

0 VOC'S

Do not use below 8 °C. Protect stored product from frost and freezing

Do not seal wet or damp surfaces

Do not start sealing if rain is imminent

**Do not use chlorine, bleach, sodium hypochlorite, acid, Paveclear or Paveclean chemicals prior to sealing with ECOSEAL Ultra HD – Imprinted concrete sealer**

The specification and coverage rates are given in good faith and are based on our experience and knowledge but without liability

As Sealers Direct has no direct control over the methods employed by the user in applying its products, any warranty either written or implied is given in good faith and can only cover the material itself

If in doubt regarding any of the above points please contact us

A Material Safety Data Sheet is available on request