

DATA SHEET

PREMIUM PAVECLEAR

DESCRIPTION

Broad spectrum weed, moss and lichen killer and inhibitor.

USES

This product has been specially formulated for use as a weed and moss killer treatment during the refurbishment of block paving.

Also keeps unsealed block paving weed and moss free when used as part of a maintenance program

Can also be used on patios, shingle and aggregate.

THIS PRODUCT IS TO BE DILUTED WITH WATER BEFORE USE

DILUTION RATE

1:9. Pour 1 ltr of product into a plastic watering can and top up with 9 ltr of water.

COVERAGE

Apply liberally with plastic watering can & rose head over surface. Leave to dry.
20ltr of diluted product covers approximately 50 square metres
Enough concentrate to cover approximately 500 square metres

**NOTE: This product has been formulated for application by watering can.
Garden chemical sprayers will not produce the desired results.**

APPLICATION

ESTABLISHED UNSEALED BLOCK PAVING.

Pressure clean/ flat surface clean paving, Soak paving with PREMIUM PAVECLEAR,
When dry, re-sand joints with kiln dried sand.

NEW UNSEALED BLOCK PAVING. (no existing growth)

Soak paving with PREMIUM PAVECLEAR every 3 months to prevent growth.

(Do not use on Tarmac)

COLOUR RANGE

Clear.

PACK SIZE

20 litre containers.

CLEANING

For cleaning equipment use water

PRECAUTIONS

WARNING: DO NOT ALLOW CONTACT WITH ACID (CREATES GAS)

CAUTION:

Wear protective clothing, gloves, and goggles.

Do not allow contact with borders, grass & flowers you wish to survive

Do not breathe vapour or spray.

Ensure good ventilation during application.

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

Remove splashes from the skin with water

Keep out of reach of children.

Do not use near fishponds.

Toxic to aquatic organisms.

May cause long term adverse effects in the aquatic environments.



The specification and coverage rates are given in good faith and are based on our experience and knowledge but without liability.

As Sealers Direct Paving Services has no direct control over the methods employed by the user in applying its products, any warranty either written or implied is given in good faith and can only cover the material itself.

If in doubt regarding any of the above points, please contact our technical services department for advice.

A Material Safety Data Sheet is available on request.

Sealers Direct Paving Services
1 Slough Lane, Upton, Poole, Dorset. BH16 5NB

Nigel Haslett T: 01202 620377 M: 07899 748333
E: admin@sealersdirect.co.uk www.sealersdirect.co.uk