

## DATA SHEET

### **PREMIUM Ultra HD Natural stone sealer - (EXTERIOR USE ONLY) (Ultra High solids)**

#### **DESCRIPTION**

The latest high quality acrylic co-polymer resin, suspended in our unique blend of organic solvents

Designed to protect natural stone areas by repelling water, dirt, oil and fuels

Protects against frost and reduces surface deterioration

Heavy Duty

#### **USE (exterior only)**

Ready to use for sealing Sandstone, Limestone, Slate and Granite slabs or blocks.

Not for use on polished stone or glazed surfaces

#### **COLOUR RANGE**

Clear, enhances colour, restores colour

#### **PACK SIZE**

20 litre

#### **SURFACE FINISH**

##### **1 or 2 coat application**

Matt (slight sheen) 1 coat

Glossier effect 2 coats

#### **SPREADING RATE**

20-30 m<sup>2</sup> per 5 ltr when spraying, more when brushing or rolling

80-100 m<sup>2</sup> per 20 ltr when spraying, more when brushing or rolling

120-160 m<sup>2</sup> per 20 ltr 2<sup>nd</sup> coat when spraying, more when brushing or rolling

#### **DRYING TIME**

Dry to walk on usually within 2hr - During normal temps

Lower temps will extend drying time

Recoat when dry enough to walk on (1-2hr)

Do not park vehicles on surface for 48 hrs

#### **PREPARATION**

Ensure surface is clean and dry. Apply above 5°C. Do not apply to wet/ damp surfaces, if rain is imminent

#### **APPLICATION**

By course droplet low level spray, brush or roller. Avoid excess pooling and over coating.

#### **CLEANING**

For cleaning equipment use Premium SD Thinners. (Not White Spirit)

#### **PRECAUTIONS**

**Flammable.** Keep away from sources of ignition

High VOC - Do not breathe vapour or spray

Do not eat, drink, or smoke when using

Ensure good ventilation during application

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

Remove splashes from the skin with a recognized hand cleaner

Keep out of reach of children

Do not use near fishponds

Toxic to aquatic organisms  
May cause long term adverse effects in the aquatic environments

The specification and coverage rates are given in good faith and are based on our experience and knowledge but without liability

As Sealers Direct has no direct control over the methods employed by the user in applying its products, any warranty either written or implied is given in good faith and can only cover the material itself

If in doubt regarding any of the above points please contact us

A Material Safety Data Sheet is available on request