

## DATA SHEET

### PREMIUM PAVING SEALER (high solids)

#### DESCRIPTION

The latest high quality acrylic co-polymer resin, suspended in our unique blend of organic solvents. Designed to protect block paved areas by repelling water, dirt, oil and fuels. Inhibits weed and moss growth. Bonds and stabilizes jointing sand.

#### USES

Ready for use to enhance cement block paving, patios, printed concrete and stencil concrete.

#### COLOUR RANGE

Clear.

#### PACK SIZE

25 litre UN containers.

#### SURFACE FINISH

##### 1 or 2 coat application

Matt (slight sheen) 1 coat

Glossier effect 2 coats

#### SPREADING RATE

60-70 sq mtr approx per 25 ltr drum when spraying block paving.

More when brushing or rolling

80 sq mtr approx per 25 ltr drum when spraying patios, printed concrete and stencil concrete.

More when brushing or rolling.

#### DRYING TIME

Dry to walk on usually within 2hr - During normal temps.

Lower temps will extend drying time.

Recoat when ok to walk on.

Do not park vehicles on surface for 48 hrs.

#### PREPARATION

##### New blocks

Apply as soon as possible after installation. Ensure surface is clean and remove excess sand. Apply above 4°C. Do not apply to wet/ damp surfaces, if rain is imminent or if efflorescence is present.

##### Old blocks

Fully clean off surfaces with power wash, apply Premium weed and moss inhibitor. Allow to dry thoroughly and re-apply jointing sand prior to application.

#### APPLICATION

Premium Paving Sealer can be applied by course droplet low level spray, brush or roller. Avoid excess pooling and over coating.

**CLEANING**

For cleaning equipment use Premium SD Solvent. (Not White Spirit)

**PRECAUTIONS**

**Flammable.** Keep away from sources of ignition.

High VOC - Do not breathe vapour or spray.

Do not eat, drink, or smoke when using.

Ensure good ventilation during application.

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

Remove splashes from the skin with a recognized hand cleaner.

Keep out of reach of children.

Do not use near fishponds.

Toxic to aquatic organisms.

May cause long term adverse effects in the aquatic environments.

The specification and coverage rates are given in good faith and are based on our experience and knowledge but without liability.

As Sealers Direct Paving Services has no direct control over the methods employed by the user in applying its products, any warranty either written or implied is given in good faith and can only cover the material itself.

If in doubt regarding any of the above points, please contact our technical services department for advice.

A Material Safety Data Sheet is available on request.

**Sealers Direct Paving Services**

**1 Slough Lane, Upton, Poole, Dorset. BH16 5NB**

**Nigel Haslett T: 01202 620377 M: 07899 748333**

**E: [admin@sealersdirect.co.uk](mailto:admin@sealersdirect.co.uk) [www.sealersdirect.co.uk](http://www.sealersdirect.co.uk)**