

DATA SHEET

PREMIUM SF TARMAc BINDER (solvent free)

DESCRIPTION

A tough, water-based, solvent free single pack, strong flexible resin coating, which assists the court/ tarmac surface to last longer, helping to bind the top surface.

This product must be over-coated with one of our non-slip finishes/ Premium Tennis Court Paint, as Premium SF Tarmac Binder is NOT a non-slip finish.

Safe to use and environmentally friendly.

USES

As a binding aid for old/ new Tarmac/ Macadam tennis courts, multi-play areas.

Special attention to be shown to areas under trees and shaded areas.

COLOUR RANGE

Milky white in appearance, dries clear.

PACK SIZE

5-20 litre re-sealable plastic containers.

SPREADING RATE

Dependent on surface but as general guide new and sound surfaces at a coating rate of 6-8sq. metres per litre, ie. (80-100 litres per coat) and for badly fretting surfaces at 3 sq. metres per litre.

DRYING TIME

Under ambient conditions between 1-2 hours at the recommended spreading rate. For badly fretting surfaces where a thicker film is applied the drying could be 2-3 hours, depending on temperature and humidity and time of year.
(Recommended use March to September only)

PREPARATION

All surfaces are to be clean, dry and free from moss, dirt, grease and vegetative growth. Vacuum or pressure blasting with water may remove any debris. Brushing (manual or machine) may be suitable. Loose stones lying on the surface have to be removed. Any repairs to the surface must be done prior to application.

SUBSTRATE

New surfaces should be left to oxidise for at least three weeks in summer and up to 3 months during winter before applying the Premium SF Tarmac Binder.

APPLICATION

Ready for use.

Do not apply below 5°C.

Application by airless spray for best results in one coat.

Tip size in the range of 12thou – 15thou is recommended.

Roller, however thinning up to 10% maybe required.

Do not apply if the surface is damp.

Can be re-coated when dry or within a week of application.

CLEANING

Clean all equipment with water after use.

PRECAUTIONS

Keep out of reach of children.

Protect from frost.

Ensure good ventilation during application and drying time.

In case of contact with eyes wash immediately with plenty of water.

Remove splashes from skin with soap and water or a recognised hand cleaner.

Do not apply paint if there is a risk of heavy rain or frost.

Do not use near fishponds.

Toxic to aquatic organisms.

May cause long term adverse effects in the aquatic environments.

The specification and coverage rates are given in good faith and are based on our experience and knowledge but without liability.

As Sealers Direct Paving Services has no direct control over the methods employed by the user in applying its products, any warranty either written or implied is given in good faith and can only cover the material itself.

If in doubt regarding any of the above points, please contact our technical services department for advice.

A Material Safety Data Sheet is available on request.

Sealers Direct Paving Services

1 Slough Lane, Upton, Poole, Dorset. BH16 5NB

Nigel Haslett T: 01202 620377 M: 07899 748333

E: admin@sealersdirect.co.uk www.sealersdirect.co.uk