

## DATA SHEET

### Premium TARMAc Renovator Sealer - 0 VOC's (ultra high solids)

#### DESCRIPTION

A highly durable, solvent free, black ULTRA HIGH solids tarmac renovating coating/ sealer. Waterproofs to resist the formation of moss, lichen and weed growth

Prevents penetration of dirt, oil and fuels

Protects against frost and reduces surface deterioration

Environmentally friendly

#### USES

Ready for use to re-colour black Tarmac surfaces.

#### COLOUR

Black

#### PACK SIZE

20 litre containers

#### SPREADING RATE

1<sup>st</sup> coat - 60-80 square metres per 20 litres.

2<sup>nd</sup> coat - 70-100 square metres per 20 litres. Apply 2 coats for best results.

#### DRYING TIME

Dry to walk on usually within 2hr - During normal temps

Lower temps and areas in the shade will extend drying time

Recoat when dry

Do not park vehicles on surface for 48 hrs

#### PREPARATION

All surfaces should be free from loose and flaking material, dirt, grease and vegetative growth. Any debris may be removed by vacuum or pressure cleaning with air or water.

#### APPLICATION

Long pile roller/ broom/ brush

#### CLEANING

For cleaning equipment use water

#### PRECAUTIONS

NON FLAMMABLE

Do not use below 8°C. Protect stored product from frost and freezing

For your protection and safety, wear gloves, overalls, and eye protection

Keep children and animals away from sealed surface till dry

Be aware that sealed tarmac will repel surface water

Do not allow sealer to pool - Do not seal wet or damp tarmac

Do not start sealing if rain is imminent

Do not eat, drink, or smoke when using

Do not use chlorine, bleach, sodium hypochlorite, acid, Paveclear or Paveclean chemicals prior to sealing with Premium TARMAc Renovator Sealer

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

Remove splashes from the skin with soap and water

The specification and coverage rates are given in good faith and are based on our experience and knowledge but without liability

As Sealers Direct has no direct control over the methods employed by the user in applying its products, any warranty either written or implied is given in good faith and can only cover the material itself

If in doubt regarding any of the above points please contact us

A Material Safety Data Sheet is available on request

**[www.sealersdirect.co.uk](http://www.sealersdirect.co.uk)**