

## DATA SHEET

### Premium ULTRA TARMAC Renovator/Sealer (high solids) - 0 VOC's

#### DESCRIPTION

A highly durable, solvent free, black HIGH solids tarmac coating/ sealer. Waterproofs to resist the formation of moss, lichen and weed growth. Prevents penetration of dirt, oil and fuels. Protects against frost and reduces surface deterioration.

Eco and environmentally friendly.

#### USES

Ready for use to re-colour black Tarmac surfaces.

#### COLOUR RANGE

Black

#### PACK SIZE

25 litre containers.

#### SPREADING RATE

75 square metres per 25 litres. Apply 2 coats for best results.

#### DRYING TIME

Dry to walk on usually within 2hr - During normal temps.  
Lower temps and areas in the shade will extend drying time.  
Recoat when dry.  
Do not park vehicles on surface for 48 hrs.

#### PREPARATION

All surfaces should be free from loose and flaking material, dirt, grease and vegetative growth. Any debris may be removed by vacuum or pressure cleaning with air or water.

#### APPLICATION

Long pile roller/ broom/ brush

#### CLEANING

For cleaning equipment use water

#### PRECAUTIONS

NON FLAMMABLE

Do not use below 5°C. Protect stored product from frost and freezing.

For your protection and safety, wear gloves, overalls, and eye protection.

Keep children and animals away from sealed surface till dry.

Be aware that sealed tarmac will repel surface water.

Do not allow sealer to pool - Do not seal wet or damp tarmac.

Do not start sealing if rain is imminent

Do not eat, drink, or smoke when using.

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Remove splashes from the skin with soap and water.

The specification and coverage rates are given in good faith and are based on our experience and knowledge but without liability.

As Sealers Direct Paving Services has no direct control over the methods employed by the user in applying its products, any warranty either written or implied is given in good faith and can only cover the material itself.

If in doubt regarding any of the above points, please contact our technical services department for advice.

A Material Safety Data Sheet is available on request.

**Sealers Direct Paving Services**  
**1 Slough Lane, Upton, Poole, Dorset. BH16 5NB**

**Nigel Haslett T: 01202 620377 M: 07899 748333**  
**E: [admin@sealersdirect.co.uk](mailto:admin@sealersdirect.co.uk) [www.sealersdirect.co.uk](http://www.sealersdirect.co.uk)**