

DATA SHEET

Premium ULTRA ECOSEAL Paving Sealer - 0 VOC's. (Ultra high solids)

DESCRIPTION

A safe ORGANIC SOLVENT FREE sealer.

A single part acrylic co-polymer resin suspended in a non organic solvent. The latest in resin technology. Prevents penetration of dirt, oil and fuels. Protects against frost and reduces surface deterioration.

USES

Ready to use for sealing block paving, printed concrete, stencil-crete, patio slabs, concrete, interior and exterior concrete bases, architectural concrete, factory floors, warehouse floors, stone, concrete roof tiles, decking and fences.

Stabilises/ bonds jointing sand (block paving) – Inhibits weed, moss, algae and fungus growth.

COLOUR RANGE

Milky in appearance, cures clear. Enhances colour.

PACK SIZE

20 litre UN containers.

SURFACE FINISH

Matt (slight sheen) 1 coat

Glossier effect 2 coats

SPREADING RATE

Depending on surface type, porosity and application method.

Minimum 2 coats for best results.

75 sq mtr per 25ltr when spraying block paving, more when brushing or rolling.

90 sq mtr per 25ltr when spraying patios, printed concrete and stencil concrete.

More when brushing or rolling.

DRYING TIME

Dry to walk on usually within 2hr - During normal temps.

Lower temps and areas in the shade will extend drying time.

Recoat when dry.

Do not park vehicles on surface for 48 hrs.

PREPARATION – Surfaces must be clean and dry

All surfaces must be clean, dry and be free from loose and flaking material, dirt, grease and vegetative growth.

APPLICATION

Course droplet low level spray, broom, brush or roller.

Avoid over flooding surface.

* Brush, broom or roller out pooled sealer.

Do not leave pooled sealer to cure.

CLEANING - For cleaning equipment use water

PRECAUTIONS

NON FLAMMABLE

Do not use below 5°C. Protect stored product from frost and freezing.

For your protection and safety, wear gloves, overalls, and eye protection.

Keep children and animals away from sealed surface till dry.

Do not allow sealer to pool - Do not seal wet or damp surfaces.

Do not start sealing if rain is imminent

Do not eat, drink, or smoke when using.

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Remove splashes from the skin with soap and water.

Keep out of reach of children.

The specification and coverage rates are given in good faith and are based on our experience and knowledge but without liability.

As Sealers Direct Paving Services has no direct control over the methods employed by the user in applying its products, any warranty either written or implied is given in good faith and can only cover the material itself.

If in doubt regarding any of the above points, please contact our technical services department for advice.

A Material Safety Data Sheet is available on request.

Sealers Direct Paving Services

1 Slough Lane, Upton, Poole, Dorset. BH16 5NB

Nigel Haslett T: 01202 620377 M: 07899 748333

E: admin@sealersdirect.co.uk www.sealersdirect.co.uk