

DATA SHEET

PREMIUM WS TARMAc BINDER solvent based

DESCRIPTION

A tough, solvent-based, single pack, strong flexible resin coating which assists the court/ tarmac surface to last longer, helping to bind the top surface.

This product must be over-coated with one of our non-slip finishes/ Premium Tennis Court Paint, as Premium Tarmac Binder is NOT a non-slip finish.
Based on white spirit solvent.

USES

As a binding aid for old/ new Tarmac/ Macadam tennis courts, multi-play areas.
Special attention to be shown to areas under trees and shaded areas.

COLOUR RANGE

Clear

PACK SIZE

5 - 25 litre metal containers.

SPREADING RATE

Dependent on surface, but as a general guide new and sound surfaces at a coating rate of 6-8 sq metres per litre, ie. (75 -100 litres per coat) and for badly fretting surfaces at 3 sq. metres per litre.

DRYING TIME

Under ambient conditions between 1-2 hours at the recommended spreading rate.
For badly fretting surfaces where a thicker film is applied the drying could be 2-3 hours, depending on temperature and humidity and time of year. Can be applied in less favourable weather conditions than water based paints.

PREPARATION

All surfaces are to be clean, dry and free from moss, dirt, grease and vegetative growth. Vacuum or pressure blasting with water may remove any debris. Brushing (manual or machine) may be suitable. Loose stones lying on the surface have to be removed. Any repairs to the surface must be done prior to application.

SUBSTRATE

New surfaces should be left to oxidise for at least three weeks in summer and up to 3 months during winter before applying the Tarmac Binder.

APPLICATION

Ready for use.

Do not apply below 5°C.

Airless spray for best results.

Application by airless spray for best results in one coat.

Tip sizes in the range of 12thou – 15thou are recommended.

Roller, however thinning up to 10% with white spirit maybe required.

Do not apply if the surface is damp.

Can be re-coated when dry or within a week of application.

CLEANING

Clean all equipment with white spirit after use.

PRECAUTIONS

Flammable keep away from sources of ignition.

Ensure good ventilation during application.

In case of contact with eyes rinse immediately with plenty of water and seek medical advice.

Remove splashes from the skin with a recognized hand cleaner.

Keep out of reach of children.

Do not use near fishponds.

Toxic to aquatic organisms.

May cause long term adverse effects in the aquatic environments.

SOLVENT-BASED PAINTS

Solvent vapour (white spirit) does not present a problem providing they are correctly applied in accordance with the can instruction, or product data sheet.

The specification and coverage rates are given in good faith and are based on our experience and knowledge but without liability.

As Sealers Direct Paving Services has no direct control over the methods employed by the user in applying its products, any warranty either written or implied is given in good faith and can only cover the material itself.

If in doubt regarding any of the above points, please contact our technical services department for advice.

A Material Safety Data Sheet is available on request.

Sealers Direct Paving Services

1 Slough Lane, Upton, Poole, Dorset. BH16 5NB

Nigel Haslett T: 01202 620377 M: 07899 748333

E: admin@sealersdirect.co.uk www.sealersdirect.co.uk